No: 10140-200

VIO® 200 D

The electrosurgical unit for medical specialities -modular with individual configurations.

- Automatic output dosage for all regulative technologies
- Precise power output adjusted to the individual indication
- New and improved CUT and COAG functions
- Variable configuration with socket modules
- Upgrades for specific medical specialties are possible at any time
- Simple, interactive and safe operation using the TFT display and FocusView
- Display-supported neutral electrode safety system NESSY provides interactive assistance when positioning the return electrode
- Individually configurable programs in simple text: switch on the unit and begin working
- ReMode function: "remote control" via the handle or foot switch straight from the sterile field
- Designed to provide solutions for specific medical indications in the medical fields gastroenterology, ENT, and bronchoscopy, and for use in operative outpatient procedures

Technical Data

Power output	
Maximum CUT output	200 watt at 500 ohm
Maximum COAG output	up to 120 watt
Safety system	NESSY
Frequency	350 kHz

Mains connection	
Power frequency	50 / 60 Hz
Power input during stand-by	40 Watts
Power input during max RF output	500 watt / 920 VA
System voltage	100-120 / 220-240 V
Potential equalization connection	yes

Dimensions and weight	
Width x Height x Depth	410 x 165 x 380 mm
Weight	9,5 kg

Additional product information	
Packaging unit	1 Piece

Standards	
Classification acc. to 93/42 EWG	IIb
Protection category acc. to EN 60 601-1	I
Type acc. to EN 60 601-1	CF
Category acc. to UMDNS	11-490